

Topeka school house construction agreement

In this 1857 document, Charles H. Branscomb, acting on behalf of the New England Emigrant Aid Company, contracted with Abner Doane to construct a school house on Harrison Street in Topeka, Kansas Territory. Detailed construction specifications for the school house were included as part of the agreement.

Creator: New England Emigrant Aid Company

Date: June 9, 1857

Callnumber: History. Topeka #646 Box 36 Folder 5

KSHS Identifier: DaRT ID: 90154

Item Identifier: 90154

www.kansasmemory.org/item/90154

KANSAS HISTORICAL SOCIETY



Specification for a school Moure bolor beauth B. Const Low number 14 19 14 14 manie propher for The Buckeng is to be there, fine feet long disordiffeet wice to The Buckeng is to be there, fine feet long disordiffeet wice to The Buckeng is to be there, fine feet long disordiffeet wice to The Buckeng is to be there, fine feet long disordiffeet wice to The Buckeng is to be there, fine feet long disordiffeet wice to The Buckeng is to be there, the feet long disordiffeet wice to The Buckeng is to be there, as the feet feet of point to to the foundation water from the feet general benefit as to be the receiver water from the least of the feet floor the Steel the return water from the least of the feet floor the the theorem in the feeth Story The side street water of the decent of the feeth floor the the theorem in the feeth Story The side street water of the decent of the feeth they, then the in the second of the terms may be the feeth they, then the in the second of the the placed with the street on Checken in the second of the the placed with the street on Checken in the second of the placed with the street of the feeth of the feest floor to be placed to whe floor place to be floored to when four the placed from the theory of the feeth of the floor of the mile of soul to the placed the the be floored to what the feeth floored to the the floor builting is to the the theory to the medial of seek the a briffing is to the the theory to the medial of seek the a briffing is to the the theory the medial of seek the a briffing is to the the theory to the medial of seek the a briffing is to the theory to the medial of seek the a briffing is to the theory to the medial of seek the a briffing is to the theory to the medial of seek the a briffing is to the theory to the medial of seek the a briffing is to the seek the medial of the		
Specification for a school Moure bolor built be led no Board of Special and the tember of hours, on the service for the Men suggest that Gent book number we have the tember of hours for the Men suggest that Gent of mounts for the Men suggest that Gent be possed the Mental of the long hours for the wall, that her long hours the pount grate, The foundation wall a high of the feet less of fail is to be found for the pount grate. The foundation wall a high of the feet less of fail is to be for the best of the hours which to be be propely made up the heart malerial— All founds to be he propely made up the heart floor the foundation who to be propely made up the forest floor the form white made of the forest floor the forest walls returned to the forest floor the forest walls on the the tenser walls from the locate of the forest floor the forest walls on the therm with some the stand was the forest from the forest with the forest with the forest for the forest with the forest of the forest with the forest with the forest of the forest with the forest of the forest with t	His X was	
Specification for a school Boun to be built to be below to have some of Sophia in the limby glavers on Harrison to his host host munice up. My. My in case signed for the Mes Sing land to migrant level Company. The Building is to be their, fine feet long divertified under the line some heft. The foundation was a high so the first line of point is to be to the found for the point grate. The foundation was a high so the first line of point is to be to the chart high to be because of the feest malarise. Ille focus to to be properly ment explished malarise. Ille focus to to constructed of grate back of the feest floor Whe hoof are to be constructed of grate back of one to be 12 inches with the treatment was the feest of the feest floor Whe host there is the feest of the feest floor the transment of the feest story. The situation was to feest of the secret story are to be swicked in the waster or the story that was an the secret story. The situation is the secret sing. I have to be proved to the waster or the flow of the manager that the secret will be proved to the floor to be placed in the waster or the points of the private floor to be placed to the the form of the points of the private floor to be placed to the total Cheming storing the points to the course of having some bodying is to men through the modelle of seale like to the same bodying is to men through the modelle of seale tier. Nearly the sheeter waster waster to and a sealer of having some bodying is to men through the modelle of seale tier. Nearly the sheeter waster waster to and a sealer of having some bodying is to men through the modelle of seale tier.	I de internet in the many of the part	
Clover Boans of Pipelia in the temps of hours, our harreson him to bok number the Him. 149 in case Popular for the Mes Sing Count to magrant the Company . The Building is to be thirty fine feet long divertified wide to lin Touch higher. The foundation wall or high so the feet long divertified wide to lin Touch to high. It is not to be found to the point of the foundation wall or heite so the feet being friend is to be to the feet of feet been of faile is to be to the form the found to the forth from the face of the forst floor that hold are to be stard walls from the base of the forst floor that hold the stard walls of the feet of the forst floor that hold the stard walls of the feet of the feet of the forest floor that the feet of the feet of the placed in the walls of the forest floor to be placed in the walls of the forest of the feet of the feet manner that the line from content to the feet of the feet floor to be placed in the walls of the feet of the feet floor to be placed to make from content to be placed of the feet of the feet floor to be placed to make from content to be placed of the floor from content to the floor of the feet of the floor of the feet of the floor of the floor of the feet of the floor of the feet of the floor of the		
Clover Boans of Pipelia in the temps of hours, our harreson him to bok number the Him. 149 in case Popular for the Mes Sing Count to magrant the Company . The Building is to be thirty fine feet long divertified wide to lin Touch higher. The foundation wall or high so the feet long divertified wide to lin Touch to high. It is not to be found to the point of the foundation wall or heite so the feet being friend is to be to the feet of feet been of faile is to be to the form the found to the forth from the face of the forst floor that hold are to be stard walls from the base of the forst floor that hold the stard walls of the feet of the forst floor that hold the stard walls of the feet of the feet of the forest floor that the feet of the feet of the placed in the walls of the forest floor to be placed in the walls of the forest of the feet of the feet manner that the line from content to the feet of the feet floor to be placed in the walls of the feet of the feet floor to be placed to make from content to be placed of the feet of the feet floor to be placed to make from content to be placed of the floor from content to the floor of the feet of the floor of the feet of the floor of the floor of the feet of the floor of the feet of the floor of the	Specification for a school Mouse to be built to	
The Med Sing Counce to magnetic the Company of the Med Sing Counce to magnetic the Company of the Mark to be Mark fine feet long developed under the line stones he for the walls wall be 18 with bloom the point grade. The foundation wall or he fire feet being friend the point grade. The foundation wall on he fire grade feet leep of faid is to be 18 windless think to be beneter of grade general building done Mortain is to be proporly made sught heart malwide — All foreign to to mostly from the leave of the forest floor Ather soil are to be constructed of grade break to are to be suicked with the select of the friend floor with the select walls with the select walls with the select walls with the select walls on the select with the walls on the strength of the other in the second stone the placed with the walls on the friend floor to be placed with the walls on the point, of the great floor to be placed to make from senter to early of the proof of the other from center to be placed to make from senter to early of the proof of the senter of the senter of the placed of the floor to be placed to the floor to be placed to the floor of the point of the senter of the placed of the floor of the senter of the placed of the floor of the senter of the s	Cloner Doane of Sopoeka no the tembry of hances, on Harreson	
The Buckering is to be thirty fine feet long divertified under the Trenches for the wall, that feet long divertified under the line trenches for the wall, what he is with a bloom the pount grote. The foundation wall or his wolfs good general bloom the pount grote. The foundation wall or his well good general building down to be for the history good general building. Let for which is to be from the least of the heart material - All foreign to be smooth from the least of the first floor Ather that we walled the constructed of good break of are to be 12 mother with the trees in the found of good break of are to be 12 mother with the trees we will be found they wall are the found they wall are cloved the swalls are cloved in the second stong. It is placed in the second stong of the placed in the walls are cloved in the second with the arranged in the frame should be passed in the them to the placed 20 metres from second to place to the other from the place to make the study of roofing to be placed to the other from the best to the found to the found to be placed to the second them, the found to be placed to the second them, and to the placed of the found to the second them, the found to be placed to the second them, and to be seen to the second the second them, and the second them, the found to the second the second them, the second the second the second the second them, the second the second the second the second them to the second the se	Etrot bots number 148. 147. 149 in said Popula for	
The Tracker for the wall, crate be 18 wich below the pount grade, The foundative wall a high as the gust lien of fail is to be 18 wholes thick to be built of gover query building dine - Mortain is to be propose made softhe best material - All focings to be smooth pointill All focings to be smooth pointill All the stemes walls from the least of the first floor there Note an toto constructed of good built of and to 12 motor The side of saw walls in the decend stony are to be switter in Mathens of mit water of the desire therefrom as in the first stony There are to be two flows one commoneing in the first stony Alter other in the societe stony. It be placed in the walls as Clivitit, to arranged in such manner that the stone pipes and to paint with these them mounted with Chimny stone, The faint of the pick floor to be placed to with Chimny stone, the faint of the pick floor to be placed to make from senter to could be suche from centire to center. The faister of the first stolered stone, and to be 2x12 motor, of good oat loog foods to 2x10 mich of good oat a secure of hims sens briling is to me though the module freet till how the sheeter with colour wall board not a secure to make the how the sheeter with colour wall board not a secure to make	The Meo Song Council Company - and Company	
The Tracker for the wall, crate be 18 wich below the pount grade, The foundative wall a high as the gust lien of fail is to be 18 wholes thick to be built of gover query building dine - Mortain is to be propose made softhe best material - All focings to be smooth pointill All focings to be smooth pointill All the stemes walls from the least of the first floor there Note an toto constructed of good built of and to 12 motor The side of saw walls in the decend stony are to be switter in Mathens of mit water of the desire therefrom as in the first stony There are to be two flows one commoneing in the first stony Alter other in the societe stony. It be placed in the walls as Clivitit, to arranged in such manner that the stone pipes and to paint with these them mounted with Chimny stone, The faint of the pick floor to be placed to with Chimny stone, the faint of the pick floor to be placed to make from senter to could be suche from centire to center. The faister of the first stolered stone, and to be 2x12 motor, of good oat loog foods to 2x10 mich of good oat a secure of hims sens briling is to me though the module freet till how the sheeter with colour wall board not a secure to make the how the sheeter with colour wall board not a secure to make	To by Cof 215 15 and Soprathe must supplied operated your left of	
The foundation walls walls wall be is with below the pound- grade. The foundation wall as high as the gust lien of fairl is to be 14 wiches thick to be built if good queray building done - horden is to be proposed med up the best malinal - All focings to be smooth pointed - All focings to be smooth pointed - All the retends walls from the least of the first floor the forethe of an to be leading from the least of the first floor the forethe of the side of the first floor the faith of the forether with the first walls of the star walls of the star walls of the star walls of the other of the star of the faith of the star of the star of the star of the faith of the star of the star of the faith of the star of the faith of the star of the s	The Building is to be thirty fine feet long twenty feet unde &	
The foundation wall as high as the first been of faile is to be 18 where thick to be built of gate quarage building. She have the is to be forthe from the lead of the heart malwide— Alle facings to be smooth from the lead of the first floor the food and to be constructed of growt breth & are to be 12 wicher the thrown we the first stone— The siete orner walls in the decend stone as in the forest stone that there is the feast stone with the fact to be switten in the fact of the same thethers as in the forest stone which we walls as the sound to be lead flores one Common ing in the first stone which we walls as the facility to arranged in seals meaning that the walls as the facility of the fact floor to be pleased with the walls as the facility of the fact floor to be pleased to the Stevens, shorted to be placed to the flower of the other form center to the flower of the facility of the fact floor and the stevers of having sense builting is to now through the medial of seath the or head of the should would be should be inched to work the should would be should be should be should the should would be should be should be should to the should be should the should would be should	tio ctones high.	
Let the ches thick to be beneter of good quaray builders. All facings to be mostle from the lead of the forst floor Ather All the retener water from the lead of the forst floor Ather Arif the treatment water from the lead of the forst floor Ather Arif and to be constructed of good breek of one to be 12 the horse The side of star water with decend stony are to be swicked in Norther and to be lieu fleuer one Commoneing in the forst stong. There can to be lieu fleuer one Commoneing in the forst stong. Althought to anaryce in such mennes that the swalls as Elwelit. De anaryce in such mennes that the stone proper to could the their floor bet plead to make from senter to could the first floor bet plead to make from senter to could the sucher from center the starts to rofter to be placed to where from center the starts to post out. The forst of the first stateed stones and to a extremeter of for facility of the first state and stones and to be extremed the from some from brilging is to now through the mediate of seek the and Roof but sheeke with color word town mediate manner with a	The Trenches for the walls chale be 18 wiches below the present	
Let the ches thick to be beneter of good quaray builders. All facings to be mostle from the lead of the forst floor Ather All the retener water from the lead of the forst floor Ather Arif the treatment water from the lead of the forst floor Ather Arif and to be constructed of good breek of one to be 12 the horse The side of star water with decend stony are to be swicked in Norther and to be lieu fleuer one Commoneing in the forst stong. There can to be lieu fleuer one Commoneing in the forst stong. Althought to anaryce in such mennes that the swalls as Elwelit. De anaryce in such mennes that the stone proper to could the their floor bet plead to make from senter to could the first floor bet plead to make from senter to could the sucher from center the starts to rofter to be placed to where from center the starts to post out. The forst of the first stateed stones and to a extremeter of for facility of the first state and stones and to be extremed the from some from brilging is to now through the mediate of seek the and Roof but sheeke with color word town mediate manner with a	of grade, and and would show the street will and their	
All focings to be smooth pointed - All focings to be smooth pointed - All forest floor the form the lead of the first floor the show the street of the first floor the street of the first floor the street of the street of the first floor the street of t	The foundation wall as high as the gust lien of fail is to	
All facings to be smooth pointied. All the valences walls from the level of the first floor their Noting an to be constructed of good breek & are to be 12 motors to theothers in the first store. The side of the walls in the decend story are to be swickes in theothers. I mit water of the same theothers as in the facility. There are to be live fleres one Commoneing in the first story. Who other in the Second 8 forg. It be placed in the walls as Cleveled, & arranged in such manner that the store pipes and be passed with there of the manner that the store pipes the facility of the first floor to be placed so make from senter to could still where from certic a center, the facility of the facility the condition on to be 2x12 miles, of good oak face, joints the 2x10 miles of good oak. A course of himse being bridging is to me through the module of sech tier. Koop the special worth color would bear a not a never british of it tout the sheard with color would bear a me anner with a	be 18 wiches thick to be built of gove quaray building	
All the setence walls from the level of the first floor Who are to be 12 motors to the tender with first stores on the tenders in the sector of the state walls in the stores with the sector walls of the state walls in the sector of the state of the sta		
The side strar walls in the decend sting one to be so swites in the thether in the first store. The side strar walls in the decend sting one to be swides in the thether I still wat y the same thechors as in the froit story. There are to be lieu flues one Commoneing in the first story. There are to be lieu flues one Commoneing in the walls as clevelete, the available of the start story the shall be store prosection to be proved into their mounted with the many starts. The faits of the paint floor to be placed 20 meter from center to conduct to the start of mater from center the starts of roofle to be placed to the store from center the starts of posts of the strate of the fait of the posts of the strate of		
The side error wales in the decine story are to be swites in Whether I'mt wat of the same thether as in the ferior story. There are to be lieu fleres one Commencing in the first story, other other in the second stag. It be placed in the walls as Clivabile, to arranged in such manner that the store pipes can be passed who there their mounted with thering states the fait, of the first floor to be placed 20 mehrs from center to consider of the point floor to be placed 20 mehrs from center to consider the street floor could be study a rofter to be placed to inches from center to center. The faists of the first the eard stories are to be 2x12 wither of good oat. Roof joint the 2x10 with of good oak. I course of hemis some bruting is to non through the medial of seek tile. Roof the sheelest wall color wall toant a not a treated b inches in will the sheelest wall color wall toant a not a treated b inches		
The sicle of star walls in the decence story are to be 8 wickes in the there of the wall of the store theckness as in the fewer story. There are to be two fleres one Commencing in the first story. The other in the second story - to be placed in the walls as Cliveled, & arranged in such manner that the storing storing. The fairly of the first floor to be placed 20 mehrs from senter to contar of the first floor to be placed 20 mehrs from senter to contar of the other facility and the study a ropter to be placed 16 mehrs from certic to center. The fairly of the first of seed stories are to be 2x12 metar of good oak. Roof joists the 2x10 mehrs of good oak. I course of heming some bruging is to now through the mediate of seek tier - Roof the sheeler with color wall toan's not a treated bearing in would the timinal in a good two thought manner with a		
There can to be lieu fleres one Commencing in the first story. There can to be lieu fleres one Commencing in the first story. The other in the Second story - It be placed in the walls as Clivalet, & arranged in sach manner that the store proper can be passed with these Advermounted with Chimney states, The fait, of the first floor to be placed 20 meter from center to conter - All other forest; and the study a raption to be placed 16 meter from center to center, The faith of the fait the end blower ain to be 2x12 wicker, I good out. Roof joints the 2x10 miles of good out a leaure of heming some brushing is to now through the mediate of seek tier - Roof the sheeled worth color wall town to but the treated beachs it would the thining in a good sworthmentike manner with a		
There can to be lieu fleres. One commencing ni the first story, Whe other in the second Eling - It be placed in the walls as Cliveled, & arranged in such manner that the stoine pifes can be passed into theme Adminounted with Chinney states, The foist, of the first floor to be placed 20 mehrs from senter to could - Alle other forst, and the study a rofter to be placed 16 mehrs from certic to center, The foists of the first As cent stones and to be 2x12 miles, I good oak. Roof joists the 2x10 miles of good oak. A course of heming some bridging is to now through the middle of seek ther Roof the sheeker with colour word to and that a traced benches it would the himself in a good townshmentike manner with a		
She other in the Second 8 ling - It be placed in the walls as Chocold, & arranged in such manner that the stain pepes can be passed with theme Astermounted with Chimny states The faists of the fait floor to be placed 20 mehrs from center to center - All other faits and the study a raffer to be placed 16 mehrs from center to center. The faists of The faist asseerd stories are to be 2x12 winter. I good oak floof fourth the 2x10 miles of good oak - A course of heming bond budging is to now through the mediate of each tier - Roof the sheeled worth color word to and not to treated be inches in world Alining in a good swortmentihe manner with a		
Clivated, & arranged in such manner that the stone pipes cle to passed with there Advismounted with Chimney states, The faists of the first floor to be placed 20 mehrs from center to could - All other fait and the study a rafter to be placed to makes from certic to center, The faists of the faist obseend stories and to be 2x12 miles. I good oak floof joints the 2x10 miles of good oak - A course of heming some budging is to more through the middle of each tier. Roof the sheeter with color wind boards but a traced benches it would the thinical in a good overkmentice manner with a		
the faist of the first floor to be placed 20 mehr from center to earlie - Ale other goist, and the study a rofter to be placed 16 mehr from center to be placed 16 mehrs from center to center. The faist of list & seed blower and to be 2x12 mides. If good oak. Roof faist & he 2x10 miles of good oak. Roof forth the 2x10 miles of good oak. Roof budging is to now through the mediate of each teer. Roof the sheeled works colour word to and not a treated benefit in world the thinise in a good sworkmentike manner with a		
The faists of the first floor to be placed 20 mens from senter to certie — Ale other faits and the study a vafter to be placed 16 meter from certie to center. The faists of North south of south the 2x12 miles. If good oak Roof joists the 2x10 miles of good oak — A course of heming some bridging is to now through the mediate of each tier — Roof the sheeter worth column word toans not a treated buch in word to will the manner with a		
be placed 16 miches from certic to center, The faith of the first of the first street of the 2x12 miles. If good oak Roof joists the 2x10 miles of good oak — A course of heming some bridging is to now through the middle of each tier — Roof the sheeter worth columnwel toans not a treeded buch in coult the middle of the manner with a	der be passed with these Adus movaled with Chimney states	
be placed 16 moher from certic to center. The faists of the faist & seed stories and to be 2x12 miles. If good oak Proof joists the 2x10 miles of good oak - A course of heming some budging is to now through the middle of each tier - Roof the sheeled with color word toans not a treed bucher in world & himsel in a good sworkmentike manner with a	The foists of the first floor to be placed 20 inches from elenter	
The faist of seed Stories and to be 2x12 miles. I good oak thoof joints the 2x10 miles of good oak - A course of heming some brudging is to now through the middle of seek tier - Roop the sheeled with color word toans not a traced bucher in world to himself in a good overkneutike manner with a		
Proof the sheeter with color word toans not at rece buch in will the will the manner with a second of the manner with a second of the manner with a		
Roof the sheeter with color word toans not at rece bucher in world white with a good sworkmentike manner with	The first to cerd dones are to be 2x12 meter of good oak thoof	
now the sheeter with color word board not at access buch in word the wante manner with	joists who 2 x 10 mehrs of good vall - A course of herry bond	
in could shinise in a good sworkmentike manner with	brugning is to non through the modelle of Each leer	
good quality of nothing line -	hoof are shelle with color well toan a het at thelet & hilles	
from fuely of myong line-	he tow it sunned in a good sworkmentine manner touter	
	Look Suched of while me -	



	-
Floor throughout the interior to be of good where pour	ne.
toand one wich in that new & not once brustes in will	me
longued agricold - Loan's must be well seasoned & will	1
the become to be for 28 feet high from the polycon	0
The stans to be placed on three string carriege, - steps to be	5 - W
made of times blackwalnut or oak word of good quality -	ni
The user to be of the same material & thethness _	
The cornies is to be constructore of brick as inches aloce in the	hi
front Elevaluis - Ale the wash boards are to be I nice thick	The
17 itioher will -	200
The mide dressings of the Hours securious, and to be colle finished	11
with such architance, I good blockhutenut wer scasoned as	×
possible.	
There are to be live out side plannel doors in front: 2 mines think	and there
to be of ince stadenice while pine, of a fore quality - Plannels	
To moulded on both sides - The two outsides clover in the sear &	* "
The three mills cloors, are to be ballen cloors, of price of good	37
quality, I nich thick - longwell & grande - the boards of whice sauce	Jane .
11 con on the made are not to meal so ther is width & put	
logether with screws	
Windows and conspined in the the clevation aplans the	160
East the 19/8 miles in Thethree - floss IDX 15 - The combon	min man
to be farmisted with porting beach simpromed Spring on each sally	giral
Thurson lights to be fairnesticce for the the two front doors we mide	o meete c
called upon the pont elevature	
All the street partitions selectings At Cathere for plostering	
All water & clilings throughout the interior are to have lied cong	3000
The healthing spekting win and his and and and and	
The portetions & subcliensing one to be arranged according to the	
But sicie frant doors to have mirtiene looks, with white	1
The state of the s	



me	meneral Knobs. All other cloors to here lieks with
will.	moneral Knobs Ale Cloon to be lune with sens
& mee.	balling unt some some some south soil
	The building is to be 23 feet high from the xoundsteen
the	wall - The funt stong who the feet the Locure 9/2 feet-
4-	in the clear of the state of the state of the state of the state of
	All the hawwere necessary in completing the Quietting is to
-	le of force sualety -
with	The front and of the busines is before fifth st I to be placed
1	20 ft from said 5th st- The west seine of said beileding
hinished	to to be on the line of the alley in the Kan of Sant
01	Loto - the lone of the alley in the war of said
nes this	-Cher HI Frutail
3	
. *	Abner Doang
ce	the true muches closes a site of the come of the come
Sauce	There is a line to the to be seen a great of the sail
*	there are it is not a superior to the superior of the paper of
10	to fether with some
the	Timbers are a consupring with the contino extern the
combus	Sain the 148 with in the have fees to x 18 18 1how he
asly	The formileet with poling heart vemp and spring on exclosing
well =	Thurston lighty he be priviled in the to the part is a men -
	Cald ago II me be bed
	The same of the sa
d leag.	the walls stay as a sent is a sent sent case
re	I bean medac sens stone coat
	the filling stating into me his amore notices in the
ule	And the second s
later	letteres par class to see the love of a comment











